

THAT CLAIMED IS:

1. A stator for a power generator, the stator comprising:
a plurality of laminations having a plurality of spaced-apart stator coil slots formed therein;
5 stator coil slot contents positioned in each of the plurality of stator coil slots, said stator coil slot contents including at least one stator coil;
a coil support finger plate positioned at an end portion of the plurality of stator coil slots, the coil
10 support finger plate having a base and a plurality of fingers extending outwardly from the base between the plurality of spaced-apart stator coil slots, the base including a stator slot contents support portion positioned to underlie end portions of the stator slot
15 contents and to support the end portions of the stator coil slot contents thereon so that the stator slot contents support portion defines a stator slot bottom at the coil support finger plate.
2. A stator as defined in Claim 1, wherein the end portions of the stator slot contents abuttingly contact the stator slot bottom so that the stator slot bottom of the coil support finger plate radially supports the stator
5 slot contents.
3. A stator as defined in Claim 1, wherein the stator slot contents include a layer of readily conformable material underlying the at least one stator coil to enhance protection of the at least one stator coil
5 from the outer surface of the stator slot bottom, and wherein the conformable material layer overlies and abuttingly contacts the stator slot bottom and underlies and abuttingly contacts the at least one stator coil so that the stator slot bottom supports both the conformable
10 material layer and the at least one stator coil.

000000-10000000

4. A stator as defined in Claim 3, wherein the at least one stator coil comprises a first stator slot coil overlying and abuttingly contacting the conformable material layer and a second stator slot coil overlying the first stator slot coil within the stator slot.

5. A stator as defined in Claim 1, wherein the plurality of fingers includes a plurality of spaced-apart pairs of fingers, wherein the stator coil slot bottom is positioned between each of the plurality of spaced-apart pairs of fingers, and wherein at least a pair of fingers of the plurality of fingers of the coil support finger plate each extend outwardly between an adjacent pair of end portions of the plurality of spaced-apart stator coil slots, the at least a pair of fingers including first and second fingers, distal end portions of the first finger extending outwardly a greater distance from the base than the second finger.

6. A stator as defined in Claim 5, wherein the first and second fingers are spaced-apart from each other and the greater-distance extending distal end portions of first finger being positioned adjacent distal side peripheries of each of the adjacent pair of end portions of stator coil slots and spaced-apart from distal end portions of the second finger, wherein medial portions of the first finger extends along only side peripheries of one of the end portions of the pair of stator coil slots, and wherein the second finger extends along only side peripheries of another one of the end portions of the pair of stator coil slots.

7. A stator as defined in Claim 6, wherein the distal end portions of the first finger has a first wedge land formed in a region thereof adjacent the one of the

Sub
A1

000000-4333330

Sub-1-1000

10

5

a base; and

5

10

5

contents support portion defines a stator slot bottom at the coil support finger.

11. A coil support finger plate as defined in Claim 10, wherein the stator slot contents include a layer of readily conformable material underlying the at least one stator coil to enhance protection of the at least one stator coil from the outer surface of the stator slot bottom, and wherein the conformable material layer overlies and abuttingly contacts the stator slot bottom and underlies and abuttingly contacts end portions of the at least one stator coil so that the stator slot bottom supports both the conformable material layer and the at least one stator coil.

12. A coil support finger plate as defined in Claim 11, wherein the plurality of fingers includes a plurality of spaced-apart pairs of fingers, wherein the stator coil slot bottom is positioned between each of the plurality of spaced-apart pairs of fingers, and wherein at least a pair of fingers of the plurality of fingers of the coil support finger plate each extend outwardly between an adjacent pair of end portions of a plurality of spaced-apart stator coil slots of a stator, the at least a pair of fingers including first and second fingers, distal end portions of the first finger extending outwardly a greater distance from the base than the second finger.

13. A coil support finger plate as defined in Claim 12, wherein the first and second fingers are spaced-apart from each other and the greater-distance extending distal end portions of first finger being positioned adjacent distal side peripheries of each of the adjacent pair of end portions of stator coil slots and spaced-apart from distal end portions of the second finger, wherein medial portions of the first finger extends along only side

000000-000000

peripheries of one of the pair of stator coil slots, and
 10 wherein ~~the~~ second finger extends along only side
 peripheries of another one of the pair of stator coil
 slots.

Sub 42 5 14. A coil support finger plate as defined in Claim
 13, wherein the distal end portions of the first finger
 has a first wedge land formed in a region thereof adjacent
 the one of the end portions of the pair of stator slot
 coils, and wherein the spaced-apart region between the
 distal end portions of the second finger and the distal
 end portions of the first finger define a second wedge
 land for the another one of the end portions of the pair
 of stator coil slots so that the first wedge land for the
 10 one stator slot is formed by a first pair of fingers
 having first and second fingers thereof and the second
 wedge land for the one stator slot is formed by a second
 pair of finger having first and second fingers thereof.

15 15. A coil support finger plate as defined in Claim
 14, wherein the second wedge land includes an extended
 wedge capture region positioned to capture extended
 regions of a wedge when positioned therein to thereby
 5 enhance the securing of the wedge within the first and
 second wedge lands.

16. A coil support finger plate for a stator of a
 power generator, the coil support finger plate comprising:

a base; and

5 a plurality of fingers extending outwardly from the
 base so that at least one of the plurality of fingers also
 extends between end portions of a pair of stator coil
 slots when positioned adjacent thereto, the at least one
 of the plurality of fingers having a distal end portion
 thereof being positioned adjacent distal side peripheries

000000-10000000

17. A coil support finger plate as defined in Claim 16, wherein the plurality of fingers includes a plurality of spaced-apart pairs of fingers, wherein the at least one finger comprises at least a pair of fingers, and wherein the at least a pair of fingers of the plurality of fingers of the coil support finger plate each extend outwardly between an adjacent pair of end portions of a plurality of spaced-apart stator coil slots of a stator, the at least a pair of fingers including first and second fingers, distal end portions of the first finger extending outwardly a greater distance from the base than the second finger.

18. A coil support finger plate as defined in Claim 17, wherein the first and second fingers are spaced-apart from each other and the greater-distance extending distal end portions of first finger being positioned adjacent distal side peripheries of each of the adjacent pair of the end portions of stator coil slots and spaced-apart from distal end portions of the second finger, wherein medial portions of the first finger extends along only side peripheries of one of the end portions of the pair of stator coil slots, and wherein the second finger extends along only side peripheries of another one of the end portions of the pair of stator coil slots.

Sub 73

Sub H-312 Conf'd

10

5

5

5

175

